

## Pratic Avant Fact Sheet



## Standard Features

- Single boiler system
- 4 programable, volumetric dosing touch pads
- Turn style steam knobs

## Color Options

- Black/Stainless Steel





	SAE 1 🔾	SAE 2	SAE 3
Total Wattage	2,330/2,930 watt	4,800 watt	5,350 watt
Heating Element	2,000/2600 watt	4,400 watt	5,000 watt
Boiler	6 ltr	10.5 ltr	17 ltr
Net Weight	126 lbs	159 lbs	195 lbs
Approx Ship Weight	200 lbs	230 lbs	270 lbs
Measurements W x D x H	23.2" x 22 x 22.8	31.5" x 22" x 22.8"	41" x 22" x 22.8"
Power	110 volt/ 19.4 amps	220 volt/21.4 amps	220 volt/ 23.2 amps
	220 volt/ 11.3 amps	Nema L6-30	Nema L6-30
Water Requirements  • 3/0" dedicated sold water line with shut			

- 3/8" dedicated cold water line with shut off valve and compression fitting.
- Water hardness cannot exceed 3gpg or 50ppm.
- Water softener must be installed if it exceeds the
- limits.
   Minimum incoming water flow rate of 35 GPH and

the maximum line pressure of 70 PSI/5

## **Drain Requirements**

Open gravity drain of minimum 1.25 inch within 4 feet of the machine

