






Standard Features

- Single boiler system
- 4 programable, volumetric dosing touch pads
- Preinfusion technology
- Turn style steam knobs
- Automatic (SAE) and Semiautomatic (AEP) versions
- Hot water dispenser with cool-water mixing valve (SAE 2 & 3 version)

Color Options

- Burgundy
- Inox



	SAE/AEP 1 	SAE/AEP 2 	SAE/AEP 3 
Total Wattage	1,570 watt	4,400 watt	5,350 watt
Heating Element	1,500	4,000	5,000
Boiler	5 ltr	10.5 ltr	17 ltr
Net Weight	130 lbs	151 lbs	192 lbs
Approx Ship Weight	210 lbs	230 lbs	270 lbs
Measurements W x D x H	15" x 22.25" x 22"	30" x 22.25" x 22"	39.5" x 22.25" x 22"
Power	110 volt/ 13 amps	220 volt/19.1 amps	220 volt/ 23.3 amps



Water Requirements

- 3/8" dedicated cold water line with shut off valve and compression fitting.
- Water hardness cannot exceed 3gpg or 50ppm.
- Water softener must be installed if it exceeds the limits.
- Minimum incoming water flow rate of 35 GPH and the maximum line pressure of 70 PSI/5 BAR

Drain Requirements

Open gravity drain of minimum 1.25 inch within 4 feet of the machine

